

C60 PORTABLE WALLET-SIZE POS TERMINAL

JT

It can streamline your payment business whenever and wherever necessary

MAIN FEATURES



Reliable Performance



Strong Security



Convenient Payment



E

C60

F2

F1

5 ж 6 мно

1 oz 2 ABC 3 DEF

7 PRS 8 TUV 9 WXY

Various Payment Scene



SMALL MPOS, ENDLESS POSSIBILITY C60



Processor

32bit security CPU

| 44444 | |
|-------|--|

Memory

1MB Flash, up to 8MB



Physical Keypad

10* Numeric Keys | Power key and 5*function Keys

Smart Card E

EMV L1/L2, conforming to ISO7816, 1.8V/3V/5V, synchronous&asynchronous, T=0&T=1



r (Audio



ID

Color Customized

I



Magnetic Card

Triple track, bi-directional, conforming to ISO 7810/7811/7813

C60



Display

1.7" TFT LCD (128*64)



Contactless Card

EMV Contactless L1, conforming to ISO14443 Type A/B, Mifare

Adapter 8¢

\bigcirc

Peripheral Ports

Micro USB

 $\mathbf{4}$

Battery

Li-ion Battery, 3.7V / 300mAh



Physical

(119.25*60.6*14.6) mm



Certifications

PCI PTS 6.x, EMV L1&L2, EMV Contactless L1|Visa PayWave, PayPass, CE, RoHS

Input:100-240V AC 50/60Hz, Output: 5.0V 1A



Communication BT 4.2

Accessories (-)

Charger, User guide



Environmental

" $0^{\circ}C \sim 50^{\circ}C$ operating temperature -20°C to 60°C storage temperature 10%~93% relative humidity,non-condensing"

Note:

1. This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. 2. Shenzhen JieCheng Technology Service CO., Ltd. has all the final rights of interpretation.

Shenzhen JieCheng **Technology Service CO., Ltd.**

- 22F, Building A7, Creative City Phase 1, Nanshan District, \bigcirc Shenzhen 518000, Guangdong, CHINA
- +86-0755-86561312 (\mathcal{C})



int.sales@jchsmart.com \square